

# *CMMs*

## Understanding Performance Standards



# *Understanding CMM Performance Standards*

1.0 When determining how good a coordinate measuring machine is, manufacturers rely on performance standards. These standards are useful in comparing the performance of different brands of machines, to determine, in a general way, how well the machine will measure parts, and to check that the machine is working properly.

2.0 There are different standards of measurement or calibration, however, and this often causes confusion among not only customers, but CMM manufacturers themselves. In this Tech Brief, we'll discuss how these standards differ.

3.0 Today, there are three primary standards used to verify the accuracy of measuring machine performance: ASME B89.4.1, VDI/VDE 2617, and ISO 10360. Standards organizations throughout the world agree that all three do an equally good job of measuring the overall performance of a machine. They differ principally in approach.


4.0 The chief differences are in the number of tests used to evaluate the performance of CMMs, and the way in which the performance specifications are written. The B89 standard uses five tests to evaluate length measuring performance. VDI/VDE 2617 uses three tests and ISO 10360 uses two tests, one being for the probe. B89 specifications use a single number to represent a performance range. For example, Brown & Sharpe's GAGE 2000 Measurement Station has a B89 volumetric performance specification of 0.010 mm/325 mm, the number after the slash being the length of the ball bar that was measured. This means that the range of measured lengths with the ball bar in many positions is no greater than 10 micrometers. VDI/VDE and ISO specifications represent length measuring performance as a formula.

5.0 GAGE 2000 volumetric performance is stated in the VDI/VDE format as  $U_3 = 4 + 5L/1000$ . This means that over the same measured 325 mm length, there could be an error no larger than + or - 6 (actually 5.625) micrometers.

## **6.0 VDI/VDE and ISO Performance Testing**

The VDI/VDE and ISO standards use measurements made on a calibrated step gage, or an equivalent set of gage blocks (Figure 1). In the VDI/VDE standard, the gage is measured in three types of positions: axial (U1), planar (U2), and volumetric (U3). Differences between the measured lengths and the calibrated lengths of the gage are compared in the formula  $U = a + b \times L/1000$  for the VDI/VDE specification.

7.0 The "a" term is a value representing the error made when measuring something of zero length. The "b" and "L" terms divided by 1000 represent the increase in error based on the length being measured. The formula represents a line that for zero measured length is the "a" value, 4 micrometers, for example, and goes up by a slope defined by the "b" term. The "b" term is the number of micrometers that the error increases for every 1000 millimeters of "L" length. So, the formula  $U_3 = 4 + 5L/1000$  for volumetric accuracy means that the error for zero measured length is 4 micrometers, and for every additional meter of length measured it gets 5 micrometers larger.  $U_3 = 4 + 5L$  is the way the specification is commonly referred to.



1. CLAMP    2. CLAMP HANDLE    3. COLUMN CLAMP HANDLE  
 4. COLUMN    5. M 10 SCREW    6. BASE  
 7. CENTERING HOLE    8. THUMBSCREW    9. FIXTURE  
 10. GAGE BLOCKS

*Figure 1 Gageblock Fixture*

8.0 The measurement approach is the same for the ISO standard, but the formula is changed to  $E = a + L/k$  where “k” is the “b” value for the VDI/VDE formula divided into 1000. There are no individual axial and planar specifications; they are included in the volumetric “E” specification.

## 9.0 B89 Performance Testing

The basic test of CMM performance under the B89 standard includes five measurements:

9.1 Multiple measurements of the position of a fixed ball. The range (largest minus smallest) is the repeatability of the machine.

9.2 Measurements with a step gage or laser in each axial direction. This is the linear accuracy of the machine.

9.3 Measurements of a ball bar at multiple positions and orientations in the machine’s working volume. This is the volumetric performance of the machine (Figures 2 and 3).

9.4 Measurement of the ball bar in four diagonal positions in vertical planes. In each position, the ball bar is measured with two right angle probe offsets and the difference of measured lengths is determined. The differences are compared with an offset probe performance specification. The test is sensitive to Z axis probe offset errors. This is important when using the probe at right angles to the Z axis, such as with indexing probes.

9.5 Measurement of length of a short gage block in four orientations. The measurement is compared with a bi-directional accuracy measuring capability specification. This test is sensitive to probe qualification errors.




Figure 2  
Positioning the Ballbar on  
the Ballbar Stand




Figure 3 Ballbar Positions in the Measuring Volume

## 10.0 Standard-Specific Tests

There are some other differences as well. For example, the VDI/VDE standard specifies a method for very long measurement distances, called the block method, and for the use of other gage types such as ball plates and ring gages for probe testing. Both VDI/VDE and B89 provide specific tests for machines equipped with rotary tables. The B89 standard also provides specific tests for multiple probe tips, plus laser diagonal measurements for large machines, duplex performance for dual-arm horizontal machines, and performance with heavy workpieces.

11.0 The ISO standards working group now has many of these extensions in the committee draft or balloting stage. The US B89 committee is cooperating closely with the ISO group to insure that future national and international standards are consistent.

## 12.0 Test Environment

ISO standards generally require that the operating environment for acceptance tests, especially temperature, be within limits specified by the machine manufacturer. VDI/VDE standards have a similar requirement. The B89 standard allows acceptance testing in any environment. If the environment is not within the limits specified by the machine supplier, other tests are performed to determine the effects of the environment on machine performance. The results of these tests are used to modify machine performance specifications.

## 13.0 Other Standards

There are other standards in addition to these three. The most frequently referred to are the CMM Manufacturers' Association standard, CMMMA; the Japanese standard, JIS B7440; and the British standard, BS 6808. These standards are generally limited in application, except in the countries of origin.

## 14.0 The Accuracy Issue

The most important subject now in both US and ISO standards committees is that while these performance tests provide an overall characterization of machine quality, they don't give the user enough information about how accurately the machine can measure a feature such as the diameter of a bore in an engine block. Right now, technical standards committees around the world are working to determine how to characterize what is called "task specific measurement uncertainty" as a way of describing how accurately the machine can perform a real measurement task, including the machine performance.

	<b>B89.4.1</b>	<b>VDI/VDE 2617</b>	<b>ISO 10360</b>
No. of Tests	5 (§4,9)	3 (§4,6)	2 (§4)
Specification	Single Number (§4)	Formula (§5,6,7)	Formula (§8)
Test Environment	Non-specific (§12)	Manufacturer Specific (§12)	Manufacturer Specific (§12)
Standard-Specific Tests	Tests for Multiple probe tips. Laser diagonal measurements. Duplex performance. Heavy workpiece performance. Rotary Tables.(§10)	Block Method. Ball Plates Ring Gages. Rotary Tables. (§10)	Numerous extensions in committee draft form being balloted upon. (§11)

*Figure 4 Simple Comparison of B89, VDI/VDE and ISO Performance Standards*



#### World Headquarters

Precision Park, 200 Frenchtown Road  
North Kingstown, RI 02852-1700  
Tel: (800) 766-4673  
(401) 886-2000  
Fax: (800) 933-2937  
(401) 886-2762  
Internet: [www.brownandsharpe.com](http://www.brownandsharpe.com)

#### Brown & Sharpe DEA SpA

Strada del Portone, 113  
10095 Grugliasco (TO), Italy  
Tel: 011 4025111  
Fax: 011 7803254

#### Brown & Sharpe GmbH

Siegmund-Hiepe-Straße 2-12  
D-35578 Wetzlar, Germany  
Tel: 06441 207 0  
Fax: 06441207 122

#### Brown & Sharpe Qianshao

11 Luoyang Road  
Qingdao 266045, P.R. China  
Tel: 86 532 486 2324/2534  
Fax: 86 532 485 6427

#### Brown & Sharpe - USA

North Kingstown, RI  
Tel: (800) 766-4673 Fax: (800) 933-2937  
Elgin, IL  
Tel: (847) 931-0100 Fax: (847) 931-1979  
Wixom, MI  
Tel: (248) 449-9400 Fax: (248) 449-7438  
Charlotte, NC  
Tel: (704) 525-0182 Fax: (704) 525-3154  
Cincinnati, OH  
Tel: (513) 942-0800 Fax: (513) 942-0804  
Nashville, TN  
Tel: (615) 331-0800 Fax: (615) 331-0875  
North Kingstown, RI  
(Aftermarket Services)  
Tel: (401) 886-2949 Fax: (401) 886-2959  
Wixom, MI  
(Aftermarket Services)  
Tel: (248) 449-9500 Fax: (248) 449-9559

#### Brown & Sharpe - Mexico

Garza Garcia, Mexico  
Tel: 8 338 6272 Fax: 8 338 7968

#### Brown & Sharpe - Europe

Ludwigsburg, Germany  
Tel: 07 141 8747 0 Fax: 07 141 8747 88  
Wetzlar, Germany  
Tel: 06441 207 0 Fax: 06441 207 122  
Telford, United Kingdom  
Tel: 01952 681300 Fax: 01952 681310  
Swindon, United Kingdom  
Tel: 01793 877633 Fax: 01793 877636  
Vilnius, Lithuania  
Tel: 02 771 848 Fax: 02 775 963  
Grugliasco, Italy  
Tel: 011 4025111 Fax: 011 7803254  
Milan, Italy  
Tel: 02 93549608 Fax: 02 93549609  
Pistoia, Italy  
Tel: 0573 364664 Fax: 0573 364663  
Bari, Italy  
Tel: 080 4670496 Fax: 080 4670495  
Villebon-sur-Yvette, France  
Tel: 01 69 31 84 00 Fax: 01 60 14 63 32  
Toulouse, France  
Tel: 05 61 71 37 74 Fax: 05 61 71 38 97

Lyon, France  
Tel: 04 72 57 90 24 Fax: 04 72 57 90 27  
Barcelona, Spain  
Tel: 93 5946920 Fax: 93 5946921

#### Brown & Sharpe - Asia Pacific

Minato-ku, Tokyo, Japan  
Tel: 81 3 5440 3500 Fax: 81 3 5440 5295  
Qingdao, China  
Tel: 86 532 486 2324/2534  
Fax: 86 532 485 6427  
Beijing, China  
Tel: 10 65186561 Fax: 10 65186557  
Hong Kong, China  
Tel: 2 881 8007 Fax: 2 894 8064  
Shanghai, China  
Tel: 21 6353 5159 Fax: 21 6353 7231  
Guangzhou, China  
Tel/Fax: 20 8551 1851 3407  
Mobile: 139 0846 2504  
Chongqing, China  
Mobile: 130 0167 7570/139 0642 9120  
Singapore  
Tel: 546 3819 Fax: 542 6476

Form No. 80-80326